

TATA LPT 1618 4x2

SPECIFICATIONS

 ENGINE		Parking Brake	Spring Actuated
		3	Parking Brakes
Model	Cummins B5.9	Anti-lock Braking System (ABS)	No
Capacity (cc)	5883 cc	MAJOR DIMENSIONS	
Гуре	Water Cooled Direct Injection Turbocharged, Intercooled Diesel Engine	Wheelbase (mm)	3580 mm
	3	MASS	
Power	176.9 HP @ 2500 r/min	GVM (kg)	16200 kg (GCW)
Torque Nm @ r/min	650 Nm @ 1500 r/min	Permissible Body +	
TDANICALICCION		Payload (kg)	10.93 T
TRANSMISSION		Manufactures Dans Auda	
Model	TATA GBS-600	Manufactures Rear Axle Weight (kg)	10.2 T
No. of Gears (forward & reverse)	6 F+ 1 R Manual	Manufactures Front Axle Weight (kg)	6 T
STEERING			
		FUELTANK	
- ype	Power Steering	Fuel Tank Capacity (Ltrs)	225 L
Turning Radius	9.8 m	TYRES	
DRIVE AXLE		Size & Ply rating	11R22.5 - 16 PR
Reduction Type	Single Reduction	No. of Tyres	6 + 1 Spare
Rear Axle	TATA RA - 109RR	ELECTRICALS	
CLUTCH			
		Working Voltage	24 V
Туре	Single Plate, Dry Friction Type	Batteries	2x12V, 150 Ah
	3	Air Conditioner	NA
Diameter (mm)	352 mm		
BRAKES			
Туре	Dual Circuit Full Air		

Corporate Office: TATA Motors Limited, 4th Floor, Ahura Centre, 82, Mahakali Caves Road, MIDC Andheri (East), Mumbai 400093 Website: www.tatamotors.com | Customer Helpline: cac@tatamotors.com
Tel.: 022 62407101/ 022 62407109 | Toll-free: 1800-209-7979 | Fax: 022 6240 7100

S Cam Brake