

# PRIMA 4040.K



Heavy Load  
Carrying  
Capacity



Driver  
Comfort



All-Terrain  
Application



## SPECIFICATIONS

### MODEL

PRIMA 4040.K

### ENGINE

#### Model

Cummins ISLe 400 Euro-V

#### Capacity (cc)

8900 cc

#### Type

Turbocharged

#### Max. Power

400 BHP @ 2100 r/min

#### Max. Torque

1700 Nm @ 1300-1400 r/min

### TRANSMISSION

#### Model

ZF16S1935TD with PTO

#### Shift

Manual

#### No. of Gears

16+2

#### First Gear Ratio

16.41

### REAR AXLE

#### Reduction Type

Double, TATA RA-210 HRT

#### Final Ratio

4.92

### CLUTCH

#### Type

Single

#### Diameter (mm)

430

### BRAKES

#### Type

Full Air Dual Circuit - S Cam with ABS

#### Anti-lock Braking System (ABS)

Standard

### MAJOR DIMENSIONS

#### Overall Height (mm)

3195

#### Overall Length (mm)

8038 (W/O Load Body)

#### Overall Width (mm)

2590

#### Front Overhang (mm)

1482

#### Rear Overhang (mm)

1095

#### Wheelbase (mm)

4570

### MASS

#### GVM (kg)

40000 (Design Capacity)

#### Tare - total (T) (kg)

10200 (W/O LB)

#### Manufacturers Rear Axle Weight (kg)

32500

#### Manufacturers Front Axle Weight (kg)

7500

### FUEL TANK

#### Fuel Tank Capacity (Ltrs)

365

### TYRES

#### Size & Ply Rating

12R24 18PR

### OTHERS

#### Cabin

Prima Day Cabin

#### Cabin Ventilation

HVAC

For more information, please contact:

International Business - Commercial Vehicles, A Block, Shiv Sagar Estate, Dr. Annie Besant Road, Worli, Mumbai, Maharashtra - 400 018 India.

Tel.: 91 22 67577200 | Fax: 91 22 67577225 | Website: [www.tatamotors.com](http://www.tatamotors.com)