

ΤΛΤΛ

PRIMA 4040.T

0

4040.7

Better

Loading

Capacity



TATA

PRIMA 4040.T DENTIF

A IC

Versatile Application



Driver Comfort





TATA MOTORS | Better commercial vehicles | Always

🗊 ΤΛΤΛ

SPECIFICATIONS

MODEL PRIMA 4040.T

ENGINE

Model Cummins ISLe 400 Euro-V

Capacity (cc) 8900 cc

Type Turbocharged

Max. Power 400 BHP @ 2100 r/min

Max. Torque 1700 Nm @ 1300-1400 r/min

TRANSMISSION

Model EATON FSO-1030 9s Shift Manual No. of Gears 8+1+1 First Gear Ratio 7.38

REAR AXLE

Reduction Type Double, TATA RA-210 HRT Final Ratio 5.49

CLUTCH

Diameter (mm) 430

BRAKES

Type Full Air Dual Circuit - S Cam with ABS Anti-lock Braking System (ABS) Standard

MAJOR DIMENSIONS

Overall Height (mm) 3431 Overall Length (mm) 10585 Overall Width (mm) 2585 Front Overhang (mm) 1482 Rear Overhang (mm) 3387 Wheelbase (mm) 5550

MASS

GVM (kg) 40000 (Design Capacity)

Tare - total (T) (kg) 11500

Manufacturers Rear Axle Weight (kg) 32500

Manufacturers Front Axle Weight (kg) 7500

FUEL TANK

Fuel Tank Capacity (Ltrs) 365

TYRES

Size & Ply Rating 12R24 OTHERS

Cabin Prima Slp Cabin Cabin Ventilation HVAC

For more information, please contact:

International Business - Commercial Vehicles, A Block, Shiv Sagar Estate, Dr. Annie Besant Road, Worli, Mumbai, Maharashtra - 400 018 India. Tel.: 91 22 67577200 | Fax: 91 22 67577225 | Website: www.tatamotors.com