

PRIMA 6040.S




Heavy Load
Carrying
Capacity



Driver
Comfort



Reliability &
Safety



SPECIFICATIONS

MODEL

PRIMA 6040.S

ENGINE

Model

Cummins ISLe 400 Euro-V

Capacity (cc)

8849 cc

Type

Turbocharged

Max. Power

400 BHP @ 2100 r/min

Max. Torque

1700 Nm @ 1300-1400 r/min

TRANSMISSION

Model

ZF 16 S 1830

Shift

Manual

No. of Gears

16+2

First Gear Ratio

13.8

REAR AXLE

Reduction Type

Double, TATA RA-210 HRT

Final Ratio

4.3

CLUTCH

Diameter (mm)

430

BRAKES

Type

All Air Dual Circuit - S Cam with ABS

Anti-lock Braking System (ABS)

Standard

MAJOR DIMENSIONS

Overall Height (mm)

3320

Overall Length (mm)

7415

Overall Width (mm)

2585

Front Overhang (mm)

1482

Rear Overhang (mm)

1658

Wheelbase (mm)

4275

MASS

GCM (kg)

60000 (Design Capacity)

Tare - total (T) (kg)

10050

Manufacturers Rear Axle Weight (kg)

18000

Manufacturers Front Axle Weight (kg)

7500

FUEL TANK

Fuel Tank Capacity (Ltrs)

260 Litres (std.) /

(260 + 260)=520 Litres (Optional)

For more information, please contact:

International Business - Commercial Vehicles, A Block, Shiv Sagar Estate, Dr. Annie Besant Road, Worli, Mumbai, Maharashtra - 400 018 India.

Tel.: 91 22 67577200 | Fax: 91 22 67577225 | Website: www.tatamotors.com